



Photo courtesy of Semadrones - France

# Drone Ultrasonic Thickness Gauge



# Typical Applications

Shipping

Bridges

Storage Tanks

Phone Masts

Silos

Lighting Columns

Offshore Platforms

Wind Turbines

Wireless  
Transmission  
up to 500m




Photo courtesy of AAA Drone Inspection - France

## Multigaugage 6000 Drone

The Multigaugage 6000 Drone Gauge uses Multiple Echo technology to ignore coatings up to 6 mm thick, just the metal substrate is measured. Measurements are transmitted wirelessly in real time to a PC or laptop up to 500 metres away. The system is made up of a Gauge, Gel Dispenser and Probe Holder, all designed to be very lightweight to maintain battery power. All probes have Intelligent Probe Recognition (IPR), which automatically adjusts settings in the gauge at the same time as transmitting recognition data - the result is a perfectly matched probe and gauge for enhanced performance. Additionally, the Automatic Measurement Verification System (AMVS) ensures only true measurements are displayed, even on the most heavily corroded metals. The gauge can store measurements in either a grid or string format which can then later be used in other proprietary programs.



Lightweight  
Probe



# Features

- Ignores coatings up to **6 mm thick** using **Multiple Echo**. Coating Plus+ ignores coatings up to 20 mm.
- Easily installs onto most work class drones.
- Automatic Measurement Verification System (AMVS).
- Wirelessly transmits measurements up to 500 m.
- **Works with Tritex Gel Dispenser.**
- Lightweight.
- No zeroing required.
- 10 Vdc - 32 Vdc input supply.
- Single crystal soft faced probe.
- Easy calibration.
- Intelligent Probe Recognition (IPR).
- 3 year warranty.
- Free calibration for the life of the gauge.

*“We are writing this as a testament to the quality of performance of the Multigauge 6000 Drone Thickness Gauge. Our technical team has given it high praise due its high accuracy and durability. It has impacted our field work positively.”*

Group Director, Oil and Gas,  
AERODYNE Group



# Drone Probe Holder

The Probe Holder has been designed to accurately present the probe onto the surface being measured. The connecting spring allows flexibility in all directions and the cone shaped guard ensures the probe is aligned flat onto the surface. A damping compression spring means the probe cannot be driven onto the surface too hard causing damage. The lightweight construction can be used with most drones. It is supplied with two 250 mm x 16 mm diameter carbon tubes to extend the probe out beyond the drones rotors. A specially designed system allows couplant to be pumped onto the surface of the probe using the Tritex Gel Dispenser.



Photo courtesy of Eurodrone - Netherlands



Photo courtesy of Aerialsolutions - Belgium



# Specifications

## Multigauge 6000 Gauge

\* Figures relate to most coating types

Sound Velocity Range	From 1000 m/s to 8000 m/s (0.0394 in/μs to 0.3150 in/μs)		
Single Crystal Soft Faced Probe Options	2.25 MHz	3.5 MHz	5 MHz
Probe Measurement Range	3 - 250 mm (0.120" to 10")	2 - 150 mm (0.080" to 6")	1 - 50 mm (0.040" to 2")
Probe Sizes	13 mm (0.5")	13 mm (0.5")	13 mm (0.5")
Resolution	0.1 mm (0.005") or 0.05 mm (0.002")		
Accuracy	± 0.1 mm (0.005") or ± 0.05 mm (0.002")		
Display	Communicator software on PC or laptop		
Data Transmission	Wireless RF, 2.4 GHz. Internationally Acceptable		
Coatings Range	Up to 6 mm (Standard Mode)*; up to 20 mm (Coating Plus+)*		
Power Supply	10 Vdc - 32 Vdc. Polarity Protection		
Wireless Transmission Range	Up to 500 Metres		
Dimensions (Including switches and connectors)	139 mm x 62 mm x 31 mm (5.47" X 2.44" X 1.22")		
Gauge Weight	150 g (5.3 ounces)		
Probe Weight	50 g (1.8 ounces)		
Probe Cable Weight (1.5 m)	65 g (2.3 ounces)		
Environmental	IP65. RoHS and WEEE compliant		
Operating Temperature	-10°C to +50°C (14°F to 122°F)		
Storage Temperature	-10°C to +60°C (14°F to 140°F)		



The Tritex Multigauge 6000 has been manufactured to comply with British Standard BS EN 15317:2013, which covers the characterisation and verification of ultrasonic thickness measuring equipment.

## Probe Holder

Dimensions (Flexible Cage)	110 mm x 82 mm (4.33" x 3.23")
Weight (with 2 x 250 mm sections)	105 g (3.7 ounces)

It is the responsibility of the user to ensure that all equipment is securely attached to the drone prior to flight and that all flights are carried out in a safe manner by a qualified pilot. Tritex NDT cannot be held responsible for any damage caused to the drone or by the drone to any person, structure or otherwise, whilst using the Tritex Multigauge 6000 Drone Thickness Gauge.

# Gel Dispenser

Power Supply	6 Vdc taken from Multigauge 6000 Drone Gauge
Reservoir Volume	70 ml
Flow Rate (water)	90 ml / min
Pressure (water)	9 psi
Tubing	Silicon, 2.4 mm (0.1")
Dimensions (Including switches and connectors)	110 mm x 68 mm x 45 mm (4.33" x 2.67" x 1.77")
Weight including 1.5 m Tubing (Empty)	180 g (6.35 ounces)
Environmental	IP65. RoHS and WEEE compliant
Operating Temperature	-10°C to +50°C (14°F to 122°F)
Storage Temperature	-10°C to +60°C (14°F to 140°F)



Photo courtesy of Raptor Drones - United Kingdom



## Contact

### Tritex NDT Ltd

Unit 10, Mellstock Business Park,  
Higher Bockhampton, Dorchester,  
Dorset, United Kingdom, DT2 8QJ

t: +44 (0) 1305 257160

f: +44 (0) 1305 259573

e: sales@tritexndt.com

w: www.tritexndt.com



simple . accurate . robust

## Kit Contents (Multigauge 6000):

Multigauge 6000 Drone gauge, probe, probe lead, spare membranes, membrane oil, ultrasonic gel, 15mm test block, membrane key, power supply, power - XT30 connector lead, USB - XT30 power supply, mini USB - USB adaptor, 2 x mounting clamps, manual, calibration certificate, carry case.

**Optional:** Flexible Probe Holder  
Tritex Gel Dispenser

**3 YEAR WARRANTY**

